



# GALVANIZED STEEL COMPRESSION COUPLINGS

## CONNECTOR FEATURES:

- Fittings are compatible with galvanized steel cut pipe and nipples
- Rubber gaskets ensure a water-tight seal
- Temperature Range: 14°F to 210°F
- Maximum Pressure: 125 PSI
- Approved for indoor or outdoor use
- Restrain pipe after installation to reduce vibrations

## GALVANIZED STEEL

Best for applications where conducted fluid needs inner rustproof protection

## LONG PATTERN

Provides space to connect pieces of pipe or nipples of similar diameter in a straight line



## HYDROFORMED STEEL BODY

Promotes a lightweight, structurally stiff and strong piece

## COMPRESSION END

Ensures a secure connection when installed on metal pipe



PART NO	DESCRIPTION	BX QTY	MC QTY
<b>COMPRESSION COUPLING   GALVANIZED STEEL   LONG PATTERN</b>			
160-003	1/2" COMP x COMP	10	60
160-003HP	1/2" COMP x COMP	-	5
160-004	3/4" COMP x COMP	10	40
160-004HP	3/4" COMP x COMP	-	5
160-005	1" COMP x COMP	5	40
160-005HP	1" COMP x COMP	-	10
160-006	1-1/4" COMP x COMP	4	24
160-006HP	1-1/4" COMP x COMP	-	3
160-007	1-1/2" COMP x COMP	4	24