

BRASS & PLASTIC BOILER DRAINS

MULTI-ROLE HOSE-END VALVES

HOSE THREAD OUTLET

Designed to connect to common FHT fittings and garden hoses.

MULTI-TURN HANDLE

Ergonomic design for easy on/off operation.

QUARTER-TURN HANDLE

For even faster operation, simply twist and go!



INLET TYPES

Full offering supports versatility of applications.

**APPLICABLE
CERTIFICATIONS:**



BRASS BOILER DRAINS

CONNECTOR FEATURES:

- 3/4-in Hose Thread Outlets
- Multi-turn and Quarter-turn handles
- Maximum Pressure: 125 psi
- Temperature Range: 35°F to 180°F (Multi-turn only)
- Approved for indoor or outdoor use
- For use with non-potable water



PART NO	DESCRIPTION	BX QTY	MC QTY
BOILER DRAIN BRASS HEAVY DUTY STUFFING BOX			
102-703	1/2" MIP or Sweat	12	72
102-703HN	1/2" MIP or Sweat	-	20
102-704	3/4" MIP or 1/2" FIP	12	72
102-704HC	3/4" MIP or 1/2" FIP	-	18
102-803	1/2" FIP	12	72
102-803HC	1/2" FIP	-	30
102-804	3/4" FIP	12	72



BOILER DRAIN BRASS QUARTERMASTER® - QUARTER TURN			
102-053HN	1/2" MIP or Sweat	-	20
102-054HN	3/4" MIP or 1/2" FIP	-	15



BOILER DRAIN BRASS F1807 CRIMP PEX			
102-013	1/2" PEX	12	72
102-014	3/4" PEX	12	72

BOILER DRAIN | BRASS | COMPRESSION INLET (NOT PICTURED)

102-033	1/2" (5/8" OD) Compression	12	72
---------	----------------------------	----	----



BOILER DRAIN | BRASS | EXTENDED SHANK

102-903	1/2" MIP	12	72
---------	----------	----	----



BOILER DRAIN | BRASS | PUSH FIT

1102-913	1/2" PF	10	40
1102-914	3/4" PF	10	40

PLASTIC BOILER DRAINS

FEATURES:

- 3/4-in Hose Thread Outlet
- Approved for indoor use
- For use with hot or cold water
- Maximum Pressure: 100 PSI
- Temperature Range: 33°F to 180°F



PART NO	DESCRIPTION	BX QTY	MC QTY
BOILER DRAIN CPVC			
102-223	1/2" CTS Solvent	12	72
102-223HN	1/2" CTS Solvent	-	12
102-224	3/4" CTS Solvent	12	72
102-224HN	3/4" CTS Solvent	-	12



BOILER DRAIN | ACETAL

102-503	1/2" MIP	12	72
102-504	3/4" MIP	12	72
102-603	1/2" FIP	12	72
102-604	3/4" FIP	12	72