


IN-LINE BRASS BALL VALVES

PREMIER FLOW CONTROL OFFERING

QUARTER-TURN HANDLE
For fast, efficient operation:
simply twist and go!



PACKING NUT
Lengthens the valve's
operational life.



FORGED BRASS
Supports W.O.G. operations
while resisting corrosion.

HANDLE TYPES
Stainless Steel t-handle
and locking handle
options available.

APPLICABLE CERTIFICATIONS:
See Features
at top of each page.

IN-LINE BRASS BALL VALVES

7710 SERIES

FEATURES:

- Made in Italy
- Temperature Range: -20°F to 248°F
- Maximum Pressure: 600 PSI (Size 1/4" to 1-1/4")
- Full Port for maximum flow rate
- Double O-Ring and blowout proof stem
- No Lead Brass
- CSA, NSF Certified
- UL, FM Listed

PART NO	DESCRIPTION	BX QTY	MC QTY
---------	-------------	--------	--------

7710TC | BRASS | THREADED | NICKEL PLATED


107-000NL	1/8" FIP x FIP	20	200
107-001NL	1/4" FIP x FIP	20	200
107-002NL	3/8" FIP x FIP	10	100
107-003NL	1/2" FIP x FIP	10	100
107-004NL	3/4" FIP x FIP	10	100
107-005NL	1" FIP x FIP	10	50
107-006NL	1-1/4" FIP x FIP	10	20
107-007NL	1-1/2" FIP x FIP (500 PSI)	4	20
107-008NL	2" FIP x FIP (350 PSI)	2	10

7710T | BRASS | THREADED

107-401NL	1/4" FIP x FIP	-	20
107-402NL	3/8" FIP x FIP	-	20
107-403NL	1/2" FIP x FIP	-	15
107-404NL	3/4" FIP x FIP	-	15
107-405NL	1" FIP x FIP	-	10
107-406NL	1-1/4" FIP x FIP	-	4
107-407NL	1-1/2" FIP x FIP (500 PSI)	-	4
107-408NL	2" FIP x FIP (350 PSI)	-	2

7710S | BRASS | SWEAT

107-453NL	1/2" SWT x SWT	-	15
107-454NL	3/4" SWT x SWT	-	15
107-455NL	1" SWT x SWT	-	10
107-456NL	1-1/4" SWT x SWT	-	5
107-457NL	1-1/2" SWT x SWT (500 PSI)	-	5
107-458NL	2" SWT x SWT (350 PSI)	-	2



IN-LINE BRASS BALL VALVES

7700 SERIES

FEATURES:

- Made in China
- Temperature Range: -20°F to 300°F
- Maximum Pressure: 600 PSI
- Full Port for maximum flow rate
- Packing gland and blowout proof stem
- No Lead Brass
- CSA, NSF Certified
- UL, FM Listed



PART NO	DESCRIPTION	BX QTY	MC QTY
---------	-------------	--------	--------

7700T | BRASS | THREADED

107-821NL	1/4" FIP x FIP	15	120
107-822NL	3/8" FIP x FIP	15	120
107-823NL	1/2" FIP x FIP	-	20
107-824NL	3/4" FIP x FIP	-	15
107-825NL	1" FIP x FIP	-	10
107-826NL	1-1/4" FIP x FIP	4	24
107-827NL	1-1/2" FIP x FIP	2	24
107-828NL	2" FIP x FIP	2	12
107-829NL	2-1/2" FIP x FIP	2	6
107-830NL	3" FIP x FIP	2	4
107-831NL	4" FIP x FIP	-	2

7700S | BRASS | SWEAT

107-843NL	1/2" SWT x SWT	-	25
107-844NL	3/4" SWT x SWT	-	15
107-845NL	1" SWT x SWT	-	10
107-846NL	1-1/4" SWT x SWT	4	24
107-847NL	1-1/2" SWT x SWT	2	24
107-848NL	2" SWT x SWT	2	12
107-849NL	2-1/2" SWT x SWT	2	6
107-850NL	3" SWT x SWT	2	4
107-851NL	4" SWT x SWT	-	2

7700TT | BRASS | THREADED | STAINLESS STEEL T-HANDLE

107-823THN	1/2" FIP x FIP	-	12
107-824TNL	3/4" FIP x FIP	10	60
107-824THN	3/4" FIP x FIP	-	10
107-825TNL	1" FIP x FIP	8	48

7700LH | BRASS | THREADED | LOCKING HANDLE

107-823LNL	1/2" FIP x FIP	15	120
107-824LNL	3/4" FIP x FIP	10	60
107-825LNL	1" FIP x FIP	8	48



7700SE | GALVANIZED STEEL | HANDLE EXTENSIONS*

889-823	1/2" and 3/4" Valve Handle Extension	-	50
889-825	1" and 1-1/4" Valve Handle Extension	-	50
889-827	1-1/2" and 2" Valve Handle Extension	-	50

*Handle extensions work with most 7700 Series ball valves. Contact Sales Rep for more details

IN-LINE BRASS BALL VALVES

7700 SERIES

FEATURES:

- Made in China
- Temperature Range: -20°F to 300°F
- Max Pressure: 600 PSI (excludes COMP)
- Full port for maximum flow rate
- Packing gland with blowout proof stem
- No Lead Brass
- NSF Certified



PART NO	DESCRIPTION	BX QTY	MC QTY
7700CMP BRASS COMPRESSION			
107-023NL	1/2" COMP x COMP	-	12
107-024NL	3/4" COMP x COMP	-	12
107-025NL	1" COMP x COMP	6	24
107-043NL	1/2" COMP x COMP with Drain (200 PSI)	6	36
7700TD BRASS THREADED WITH DRAIN			
107-753NL	1/2" FIP x FIP	-	10
107-754NL	3/4" FIP x FIP	-	10
107-755NL	1" FIP x FIP	-	15
7700SD BRASS SWEAT WITH DRAIN (Not Pictured)			
107-553NL	1/2" SWT x SWT	-	10
107-554NL	3/4" SWT x SWT	-	10
107-555NL	1" SWT x SWT	-	10
7700U BRASS THREADED UNION			
107-503NL	1/2" FIP x MIP Union	8	40
107-504NL	3/4" FIP x MIP Union	6	24
107-505NL	1" FIP x MIP Union	4	16
7700MF BRASS THREADED			
107-321NL	1/4" MIP x FIP	20	200
107-323NL	1/2" MIP x FIP	15	120
107-324NL	3/4" MIP x FIP	10	60
107-325NL	1" MIP x FIP	8	48
107-326NL	1-1/4" MIP x FIP	4	24
107-327NL	1-1/2" MIP x FIP	2	24
107-328NL	2" MIP x FIP	2	12

IN-LINE BRASS BALL VALVES

7690 SERIES

FEATURES:

- Made in China
- Temperature Range: -20°F to 300°F
- Maximum Pressure: 600 PSI
- Full port for maximum flow rate
- Packing gland with blowout proof stem
- No Lead Brass



PART NO	DESCRIPTION	BX QTY	MC QTY
7690T BRASS THREADED			
107-811NL	1/4" FIP x FIP	10	120
107-812NL	3/8" FIP x FIP	10	120
107-813NL	1/2" FIP x FIP	10	120
107-814NL	3/4" FIP x FIP	10	60
107-815NL	1" FIP x FIP	6	24
107-816NL	1-1/4" FIP x FIP	4	24
107-817NL	1-1/2" FIP x FIP	2	16
107-818NL	2" FIP x FIP	2	12
7690S BRASS SWEAT			
107-853NL	1/2" SWT x SWT	10	120
107-854NL	3/4" SWT x SWT	10	60
107-855NL	1" SWT x SWT	6	24
107-856NL	1-1/4" SWT x SWT	4	24
107-857NL	1-1/2" SWT x SWT	2	16
107-858NL	2" SWT x SWT	2	12
7690PX BRASS F1807 PEX			
107-342NL	3/8" PEX x PEX	10	120
107-343NL	1/2" PEX x PEX	10	120
107-344NL	3/4" PEX x PEX	10	80
107-345NL	1" PEX x PEX	6	48
107-334NL	3/4" PEX x MIP	10	80
7690MPXE BRASS F1960 PEX			
107-353NL	1/2" PEX x PEX	10	100
107-354NL	3/4" PEX x PEX	10	100
107-355NL	1" PEX x PEX	8	80
107-356NL	1-1/4" PEX x PEX	4	36
107-357NL	1-1/2" PEX x PEX	2	24
107-358NL	2" PEX x PEX	2	12
107-314NL	3/4" PEX x MIP	10	80
107-315NL	1" PEX x MIP	6	48

IN-LINE BRASS BALL VALVES

7700-NP SERIES

FEATURES:

- Made in China
- Temperature Range: -20°F to 300°F
- Maximum Pressure: 600 PSI
- Full port for maximum flow rate
- Packing gland with blowout proof stem
- CSA certified
- UL Listed
- Not for potable water applications



PART NO	DESCRIPTION	BX QTY	MC QTY
---------	-------------	--------	--------

7700TC-NP | BRASS | THREADED | CHROME PLATED | NON-POTABLE

107-821-CP	1/4" FIP x FIP	15	120
107-822-CP	3/8" FIP x FIP	15	120
107-823-CP	1/2" FIP x FIP	15	120
107-824-CP	3/4" FIP x FIP	10	60
107-825-CP	1" FIP x FIP	8	48
107-826-CP	1-1/4" FIP x FIP	4	24
107-827-CP	1-1/2" FIP x FIP	2	24
107-828-CP	2" FIP x FIP	2	12

7700LHC-NP | BRASS | THREADED | CHROME PLATED | LOCKING HANDLE | NON-POTABLE

107-821-CL	1/4" FIP x FIP	15	120
107-822-CL	3/8" FIP x FIP	15	120
107-823-CL	1/2" FIP x FIP	15	120
107-824-CL	3/4" FIP x FIP	10	60
107-825-CL	1" FIP x FIP	8	48
107-827-CL	1-1/2" FIP x FIP	2	24
107-828-CL	2" FIP x FIP	2	12

7700MF | BRASS | THREADED | NON-POTABLE

107-326	1-1/4" MIP x FIP	4	24
107-327	1-1/2" MIP x FIP	2	24
107-328	2" MIP x FIP	2	12

7700SD-NP | BRASS | SWEAT | WITH DRAIN | NON-POTABLE (Not Pictured)

107-553	1/2" SWT x SWT	15	120
107-554	3/4" SWT x SWT	10	60
107-555	1" SWT x SWT	8	48

IN-LINE BRASS BALL VALVES

7690-NP SERIES

FEATURES:

- Made in China
- Temperature Range: -20°F to 300°F
- Maximum Pressure: 600 PSI
- Full port for maximum flow rate
- Packaging gland with blowout proof stem
- Not for potable water applications



PART NO	DESCRIPTION	BX QTY	MC QTY
7690T-NP BRASS THREADED NON-POTABLE			
107-811	1/4" FIP x FIP	15	120
107-812	3/8" FIP x FIP	15	120
107-813	1/2" FIP x FIP	15	120
107-814	3/4" FIP x FIP	10	60
107-815	1" FIP x FIP	8	48
107-816	1-1/4" FIP x FIP	4	24
107-817	1-1/2" FIP x FIP	2	24
107-818	2" FIP x FIP	2	12
107-819	2-1/2" FIP x FIP	2	6
107-820	3" FIP x FIP	2	4
7690S-NP BRASS SWEAT NON-POTABLE (Not Pictured)			
107-853	1/2" SWT x SWT	15	120
107-854	3/4" SWT x SWT	10	60
107-855	1" SWT x SWT	8	48
7690LH-NP BRASS THREADED LOCKING HANDLE NON-POTABLE			
107-816-LH	1-1/4" FIP x FIP	4	24
107-817-LH	1-1/2" FIP x FIP	2	24
107-818-LH	2" FIP x FIP	2	12
7690TN-NP BRASS THREADED NICKEL PLATED NON-POTABLE (Not Pictured)			
107-811-NF	1/4" FIP x FIP	15	120
107-812-NF	3/8" FIP x FIP	15	120
107-813-NF	1/2" FIP x FIP	15	120
107-814-NF	3/4" FIP x FIP	10	60
107-815-NF	1" FIP x FIP	8	48