

# BRASS PUSH-FIT VALVES & FITTINGS

**FORGED BRASS**

Durable build to withstand daily use

**EASE-OF-USE**

Connects to Copper, PVC, and PEX tubing

**O-RING DESIGN**

Provides a water-tight seal



**REUSABLE**

Disconnect tool allows for quick and easy removal from tubing

**APPLICABLE CERTIFICATIONS:**



WETTED SURFACE CONTAINS LESS THAN 0.25% LEAD BY WEIGHT

**POLYBAG PROGRAM**



# BRASS PUSH-FIT FITTINGS

## FEATURES:

- Approved for indoor or outdoor use
- Maximum Temperature: 200°F
- Maximum Pressure: 200 PSI
- No special tools or glues required
- Ideal for tough to reach locations needing quick connections
- Can be applied to wet or dry plumbing lines
- Approved for underground applications
- Use stiffener when connecting to PEX tubing



PART NO	DESCRIPTION	INNER QTY	MC QTY
<b>COUPLING   FORGED BRASS</b>			
6630-003	1/2" PF x PF	24	96
6630-004	3/4" PF x PF	24	96
6630-005	1-in PF x PF	12	48



<b>REDUCING COUPLING   FORGED BRASS</b>			
6630-023	3/8" PF x 1/2" PF	12	48
6630-043	3/4-in x 1/2-in PF x PF	12	48
6630-054	1-in x 1/2-in PF x PF	6	24



<b>MALE ADAPTER   FORGED BRASS</b>			
6630-103	1/2-in PF x MIP	24	96
6630-104	3/4-in PF x MIP	12	48
6630-105	1-in PF x MIP	6	24



<b>REDUCING MALE ADAPTER   FORGED BRASS</b>			
6630-134	1/2-in X 3/4-in PF x PF	6	24
6630-154	1-in x 3/4-in PF x PF	6	24



<b>FEMALE ADAPTER   FORGED BRASS</b>			
6630-203	1/2-in PF x FIP	12	48
6630-204	3/4-in PF x FIP	12	48
6630-205	1-in PF x FIP	6	24



<b>FEMALE REDUCING ADAPTER   FORGED BRASS</b>			
6630-234	1/2-in x 3/4-in PF x FIP	6	24

# BRASS PUSH-FIT FITTINGS

## FEATURES:

- Approved for indoor or outdoor use
- Maximum Temperature: 200°F
- Maximum Pressure: 200 PSI
- No special tools or glues required
- Ideal for tough to reach locations needing quick connections
- Can be applied to wet or dry plumbing lines
- Approved for underground applications
- Use stiffener when connecting to PEX tubing



PART NO	DESCRIPTION	INNER QTY	MC QTY
<b>REPAIR COUPLING   FORGED BRASS</b>			
6630-303	1/2-in PF x PF	6	24
6630-304	3/4-in PF x PF	6	24
6630-305	1-in PF x PF	3	12



<b>90° ELBOW   FORGED BRASS</b>			
6631-003	1/2-in PF x PF	24	96
6631-004	3/4-in PF x PF	24	96
6631-005	1-in PF x PF	12	48



<b>REDUCING 90° ELBOW   FORGED BRASS</b>			
6631-043	3/4-in x 1/2-in PF x PF	6	24



<b>DROP EAR ELBOW   FORGED BRASS</b>			
6631-103	1/2-in PF x PF	12	48



<b>MALE ELBOW ADAPTER   FORGED BRASS</b>			
6631-203	1/2-in PF x MIP	6	24



<b>FEMALE ELBOW ADAPTER   FORGED BRASS</b>			
6631-303	1/2-in PF x FIP	6	24

# BRASS PUSH-FIT FITTINGS

## FEATURES:

- Approved for indoor or outdoor use
- Maximum Temperature: 200°F
- Maximum Pressure: 200 PSI
- No special tools or glues required
- Ideal for tough to reach locations needing quick connections
- Can be applied to wet or dry plumbing lines
- Approved for underground applications
- Use stiffener when connecting to PEX tubing



PART NO	DESCRIPTION	INNER QTY	MC QTY
---------	-------------	-----------	--------

### TEE | FORGED BRASS

6632-003	1/2-in PF x PF x PF	24	96
6632-004	3/4-in PF x PF x PF	12	48
6632-005	1-in PF x PF x PF	6	24



### REDUCING TEE | FORGED BRASS

6632-433	3/4-in x 1/2-in x 1/2-in PF x PF x PF	6	24
6632-434	3/4-in x 1/2-in x 3/4-in PF x PF x PF	6	24
6632-443	3/4-in x 3/4-in x 1/2-in PF x PF x PF	12	48



### CAP | FORGED BRASS

6633-003	1/2-in PF	24	96
6633-004	3/4-in PF	12	48
6633-005	1-in PF	12	48



### REPAIR HOSE | FORGED BRASS (Not Pictured)

6635-003	1/2-in x 12-in PF x PF	8	32
6635-004	3/4-in x 12-in PF x PF	8	32



### DISCONNECT CLIP | DURABLE PLASTIC

6636-003	1/2-in	-	48	192
6636-004	3/4-in	-	48	192
6636-005	1-in	-	24	96



### STIFFENER | DURABLE PLASTIC

6636-103	1/2-in	-	48	192
6636-104	3/4-in	-	48	192
6636-105	1-in	-	24	96

### POLYBUTYLENE COUPLING | FORGED BRASS

6637-003	1/2-in	PF x PB	12	48
6637-004	3/4-in	PF x PB	6	24

# BRASS PUSH-FIT FITTINGS

## FEATURES:

- Approved for indoor or outdoor use
- No special tools or glues required
- Ideal for tough to reach locations needing quick connections
- Use stiffener when connecting to PEX tubing
- Working Temperature: 72°F (Excludes FFS)
- Working Pressure: 72 PSI (Excludes FFS)



PART NO	DESCRIPTION	INNER QTY	MC QTY
---------	-------------	-----------	--------

### 7690PF BALL VALVES | BRASS

1107-063	1/2-in PF x PF	12	48
1107-064	3/4-in PF x PF	12	48
1107-065	1-in PF x PF	6	24



### BOILER DRAIN | BRASS

1102-913	1/2" PF	10	40
1102-914	3/4" PF	10	40



### FROST FREE SILLCOCK | BRASS | CHROME PLATED | ANTI-SIPHON | MULTI-TURN

1104-591	1/2" PF x 4"	-	10
1104-593	1/2" PF x 6"	-	8
1104-595	1/2" PF x 8"	-	10
1104-597	1/2" PF x 10"	-	10
1104-599	1/2" PF x 12"	-	10



### NO KINK HOSE BIBB | BRASS | QUARTER TURN

1102-653	1/2" PF	10	40
1102-654	3/4" PF	10	40



### HOSE BIBB | BRASS | QUARTER TURN

1103-153	1/2" PF	10	40
1103-154	3/4" PF	10	40



### SILLCOCK | BRASS | MULTI-TURN

1108-603	1/2" PF	8	32
1108-604	3/4" PF	8	32



### SILLCOCK | BRASS | MULTI-TURN

1102-211	1/2" PF	10	40
----------	---------	----	----