

ONE-PIECE BRASS GAS VALVES PRECISION ENGINEERING

DESIGNED FOR OUTSTANDING SERVICE

MINIMIZE POTENTIAL LEAK POINTS

ProLine Series One-Piece Gas Valves are a best-in-class offering for gas flow control needs. Our fully certified and precisely engineered offering demonstrates a commitment to gas valves that are both long-lasting and reliable performance. For more information, please contact your local sales representative.

QUARTER-TURN HANDLE

For fast, efficient operation: simply twist and go! Yellow



APPLICABLE CERTIFICATIONS:





FORGED BRASS

Supports W.O.G. operations while resisting corrosion.



SAFETY HANDLE OPTION

Prevents accidental opening and closing of the valve.





INLET TYPES

FIP, MIP, and Flare connections are available.

ONE-PIECE BRASS GAS VALVES

7701G SERIES GAS VALVE

CONNECTOR FEATURES:

- Made in Italy
- Maximum Pressure: 125 PSIWorking Pressure: 14 PSI
- Temperature: -20°F to 125°F
- Working Temperature: 73°F
- Certified to meet all safety and operation excellence standards.



PART NO	DESCRIPTION	BX QTY	MC QTY
7701G BRASS LEVE	R HANDLE		
110-522	3/8" FIP x FIP	10	100
110-522HC	3/8" FIP x FIP	-	10
110-523	1/2" FIP x FIP	10	100
110-523HC	1/2" FIP x FIP	-	30
110-524	3/4" FIP x FIP	10	100
110-524HC	3/4" FIP x FIP	-	20



7701GT BRASS TEE HANDLE			
111-523	1/2" FIP x FIP	10	100
111-524	3/4" FIP x FIP	10	100
111_595	1" EID v EID	6	30



7701GFH BRASS FLAT HEAD			
113-523	1/2" FIP x FIP	10	100
113-524	3/4" FIP x FIP	10	100
113-525	1" FIP x FIP	6	30
113-526	1-1/4" FIP x FIP	4	20



7701GST BRASS SIDE TAP			
110-553	1/2" FIP x FIP - Side Tap	10	100
110-554	3/4" FIP x FIP - Side Tap	10	100
110-555	1" FIP x FIP - Side Tap	6	30



ONE-PIECE BRASS GAS VALVES

7701G SERIES GAS VALVE

CONNECTOR FEATURES:

- Made in Italy
- Maximum Pressure: 125 PSIWorking Pressure: 14 PSI
- Temperature: -20°F to 125°F
- Working Temperature: 73°F
- Certified to meet all safety and operation excellence standards.



PART NO	DESCRIPTION	BX QTY	MC QTY
7701GFL BRASS			
116-502	3/8" Flare x Flare	10	100
116-503	1/2" Flare x Flare	10	100
116-504	5/8" Flare x Flare	10	100
7701GFLM BRASS	(Not Pictured)		
116-512	3/8" Flare x 1/2" MIP	10	100
116-513	1/2" Flare x 1/2" MIP	10	100
7701GFLF BRASS			
114-522	3/8" Flare x 1/2" FIP	10	100
114-523	1/2" Flare x 1/2" FIP	10	100
114-544	1/2" Flare x 3/4" FIP	10	100
114-543	15/16" Flare x 1/2" FIP	10	100
114-524	15/16" Flare x 3/4" FIP	10	100
7701GFLF BRASS	ANGLE VALVE		
114-533	3/8" Flare x 1/2" FIP	10	100
114-534	15/16" Flare x 3/4" FIP	10	100



117-592	9/16" - 24 Fine Thread Flare x 1/2" FIP	10	100



7701GTX | BRASS | TEXAS PATTERN

115-503	1/2" FIP x Texas Pattern	10	100



ONE-PIECE BRASS GAS VALVES

7701G SERIES GAS VALVE

CONNECTOR FEATURES:

- Made in Italy
- Maximum Pressure: 200 PSIWorking Pressure: 0.5 PSI
- Temperature: -4°F to 140°F
- Working Temperature: 72°F
- Push-To-Turn safety handle for additional flow control



PART NO	DESCRIPTION	BX QTY	MC QTY	
7701GSO SERIES GAS VALVE SUREOFF TAMPER RESISTANT SAFETY HANDLE				
210-522RP	3/8" FIP x FIP - (Clamshell)	-	15	
210-523HC	1/2" FIP x FIP	-	30	
210-523RP	1/2" FIP x FIP - (Clamshell)	-	15	
210-524HC	3/4" FIP x FIP	-	20	
210-524RP	3/4" FIP x FIP - (Clamshell)	-	10	

