

# ANGLE & STRAIGHT BRASS SUPPLY STOPS 1/4-TURN & MULTI-TURN

**CHROME PLATING**  
 Supports corrosion resistance from common household cleaners.



**LOOSE KEY**  
 Supports secure water usage by removing the handle.



**DUAL-OUTLET MODELS**  
 Supports connections to multiple appliances.

**APPLICABLE CERTIFICATIONS:**



WETTED SURFACE CONTAINS LESS THAN 0.25% LEAD BY WEIGHT

# 1/4-TURN ANGLE SUPPLY STOPS

## CONNECTOR FEATURES:

- Lead Free
- Certified NSF 61
- Maximum Pressure: 125 PSI
- Working Temperature: 72°F
- Double O-Ring for safety



PART NO	DESCRIPTION	BX QTY	MC QTY
<b>COMPRESSION X COMPRESSION</b>			
190-022HC	3/8" OD X 3/8" OD ANGLV - CHROME	-	12
190-031HC	5/8" OD X 1/4" OD ANGLV - CHROME	-	12
190-032HC	5/8" OD X 3/8" OD ANGLV - CHROME	-	16
190-032LK	5/8" OD X 3/8" OD ANGLV - CHROME LOOSE KEY	-	12
190-033HC	5/8" OD X 1/2" OD ANGLV - CHROME	-	12
<b>COMPRESSION X SLIP JOINT (Not Pictured)</b>			
190-037HC	5/8" OD X 7/16" SL ANGLV - CHROME	-	12
<b>FIP X COMPRESSION</b>			
190-222HC	3/8" FIP X 3/8" OD ANGLV - CHROME	-	12
190-231HC	1/2" FIP X 1/4" OD ANGLV - CHROME	-	12
190-232HC	1/2" FIP X 3/8" OD ANGLV - CHROME	-	16
190-232LK	1/2" FIP X 3/8" OD ANGLV - CHROME LOOSE KEY	-	12
190-233HC	1/2" FIP X 1/2" OD ANGLV - CHROME	-	12
<b>FIP X SLIP JOINT (Not Pictured)</b>			
190-237HC	1/2" FIP X 7/16" SL ANGLV - CHROME	-	12
<b>SWEAT X COMPRESSION (Not Pictured)</b>			
190-432HC	1/2" SWT X 3/8" OD ANGLV - CHROME	-	16
<b>CPVC X COMPRESSION (Not Pictured)</b>			
190-732HC	1/2" CPVC X 3/8" OD ANGLV - CHROME	-	10
<b>F1807 CRIMP PEX X COMPRESSION</b>			
190-832HC	1/2" PEX X 3/8" OD ANGLV - CHROME	-	10
<b>F1960 COLD EXPANSION PEX X COMPRESSION</b>			
190-862HC	1/2" PEX X 3/8" OD ANGLV - CHROME	-	10
<b>PUSH FIT X COMPRESSION</b>			
1190-931HC	1/2" PF X 1/4" OD ANGLV - CHROME	-	10
190-931LK	1/2" PF X 1/4" OD ANGLV - CHROME LOOSE KEY	-	12
1190-932HC	1/2" PF X 3/8" OD ANGLV - CHROME	-	10
190-932LK	1/2" PF X 3/8" OD ANGLV - CHROME LOOSE KEY	-	12
<b>PUSH FIT X SLIP JOINT (Not Pictured)</b>			
190-937HC	1/2" PF X 7/16" SLIP ANGLV - CHROME	-	10

# 1/4-TURN STRAIGHT SUPPLY STOPS

## CONNECTOR FEATURES:

- Lead Free
- Certified NSF 61
- Maximum Pressure: 125 PSI
- Working Temperature: 72°F
- Double O-Ring for safety



PART NO	DESCRIPTION	BX QTY	MC QTY
<b>COMPRESSION X COMPRESSION</b>			
191-022HC	3/8" OD X 3/8" OD STRVLV - CHROME	-	12
191-032HC	5/8" OD X 3/8" OD STRVLV - CHROME	-	16
<b>RETRO FIT X COMPRESSION (Not Pictured)</b>			
191-099HC	RETRO 3/8" FE X 3/8" OD STRVLV - CHROME	-	16
<b>FIP X COMPRESSION</b>			
191-222HC	3/8" FIP X 3/8" OD STRVLV - CHROME	-	12
191-232HC	1/2" FIP X 3/8" OD STRVLV - CHROME	-	12
191-233HC	1/2" FIP X 1/2" OD STRVLV - CHROME	-	12
<b>FIP X SLIP JOINT (Not Pictured)</b>			
191-237HC	1/2" FIP X 7/16" SLIP STRVLV - CHROME	-	12
<b>SWEAT X COMPRESSION (Not Pictured)</b>			
191-432HC	1/2" SWT X 3/8" OD STRVLV - CHROME	-	12
<b>F1807 CRIMP PEX X F1807 CRIMP PEX</b>			
191-622HC	1/2" PEX X 1/2" PEX STRVLV - CHROME	-	16
<b>CPVC X COMPRESSION</b>			
191-732HC	1/2" CPVC X 3/8" OD STRVLV - CHROME	-	10
<b>F1807 CRIMP PEX X COMPRESSION (Not Pictured)</b>			
191-832HC	1/2" PEX X 3/8" OD STRVLV - CHROME	-	10
<b>F1960 COLD EXPANSION PEX X COMPRESSION</b>			
191-862HC	1/2" PEX X 3/8" OD STRVLV - CHROME	-	10
<b>PUSH FIT X COMPRESSION</b>			
1191-931HC	1/2" PF X 1/4" OD STRVLV - CHROME	-	10
1191-932HC	1/2" PF X 3/8" OD STRVLV - CHROME	-	10
<b>PUSH FIT X SLIP JOINT (Not Pictured)</b>			
191-937HC	1/2" PF X 7/16" SLIP STRVLV - CHROME	-	10

# MULTI-TURN ANGLE & STRAIGHT SUPPLY STOPS

## CONNECTOR FEATURES:

- Lead Free
- Certified NSF 61
- Maximum Pressure: 125 PSI
- Working Temperature: 72°F
- Double O-Ring for safety



PART NO	DESCRIPTION	BX QTY	MC QTY
<b>COMPRESSION X COMPRESSION (Not Pictured)</b>			
192-032HC	5/8" OD X 3/8" OD ANGLV - CHROME	-	12
192-032LK	5/8" OD X 3/8" OD ANGLV - CHROME LOOSE KEY	-	12
<b>COMPRESSION X SLIP JOINT</b>			
192-037HC	5/8" OD X 7/16" SL ANGLV - CHROME	-	12
<b>FIP X COMPRESSION</b>			
192-122HC	3/8" FIP X 3/8" OD ANGLV - CHROME	-	12
192-132HC	1/2" FIP X 3/8" OD ANGLV - CHROME	-	12
192-132LK	1/2" FIP X 3/8" OD ANGLV - CHROME LOOSE KEY	-	12
<b>FIP X SLIP JOINT (Not Pictured)</b>			
192-137HC	1/2" FIP X 7/16" SL ANGLV - CHROME	-	12
<b>CPVC X COMPRESSION (Not Pictured)</b>			
192-732HC	1/2" CPVC X 3/8" OD ANGLV - CHROME	-	10
<b>F1807 CRIMP PEX X COMPRESSION</b>			
192-832HC	1/2" PEX X 3/8" OD ANGLV - CHROME	-	30
<b>COMPRESSION X COMPRESSION</b>			
193-032HC	5/8" OD X 3/8" OD STRVLV - CHROME	-	12
<b>FIP X COMPRESSION (Not Pictured)</b>			
193-132HC	1/2" FIP X 3/8" OD STRVLV - CHROME	-	12

# DUAL OUTLET SUPPLY STOPS

## CONNECTOR FEATURES:

- Lead Free
- Certified NSF 61
- Maximum Pressure: 125 PSI
- Working Temperature: 72°F
- Double O-Ring for safety



PART NO	DESCRIPTION	BX QTY	MC QTY
<b>COMPRESSION X COMPRESSION X COMPRESSION   1/4-TURN (Not Pictured)</b>			
194-321HC	5/8" OD X 3/8" OD X 1/4" OD ANGLV - CHROME	-	10
194-322HC	5/8" OD X 3/8" OD X 3/8" OD ANGLV - CHROME	-	10
<b>FIP X COMPRESSION X COMPRESSION   1/4-TURN</b>			
195-321HC	1/2" FIP X 3/8" OD X 1/4" OD ANGLV - CHROME	-	10
195-322HC	1/2" FIP X 3/8" OD X 3/8" OD ANGLV - CHROME	-	10
<b>COMPRESSION X COMPRESSION X COMPRESSION   MULTI-TURN</b>			
196-322HC	5/8" OD X 3/8" OD X 3/8" OD ANGLV - ROUGH BRASS	-	10
<b>COMPRESSION X COMPRESSION X COMPRESSION   1/4-TURN</b>			
197-321HC	5/8" OD X 3/8" OD X 1/4" OD 2DHL - ROUGH BRASS	-	30
197-322HC	5/8" OD X 3/8" OD X 3/8" OD 2DHL - ROUGH BRASS	5	30